

INSTALLATION INSTRUCTIONS

Oval Wall-Hung Basin 52cm Gloss White
Product code: AC202802W

Important safety information

Installation must be completed by a competent person. The installer is responsible for checking the wall, worktop or furniture, selecting suitable fixings and complying with local plumbing and building requirements. Ceramic is heavy and can be damaged by impact or uneven tightening; use two people where needed.

Before you begin

Check the SKU and finish, compare the product with the technical specification, and confirm that the tap, waste, trap, sealant and fixings are suitable. Protect the basin and surrounding surfaces throughout installation.

Installation sequence

- 1 Read the technical specification and inspect the basin before installation. Do not install a chipped, cracked or damaged product.
- 2 Verify the mounting height, fixing centres and service positions. The supporting wall must be structurally suitable; tiles or plasterboard alone must not carry the load.
- 3 Locate concealed pipes and cables before drilling. Use corrosion-resistant fixings suitable for the wall construction and the basin load.
- 4 Offer the basin to the wall, level it and tighten fixings evenly. Use protective washers where required and never overtighten against the ceramic.
- 5 Apply neutral-cure sanitary silicone at the wall junction, leaving any drainage or ventilation gaps required by the installation design.
- 6 Connect the waste and trap without placing strain on the ceramic. Complete tap connections in accordance with the tap manufacturer's instructions.
- 7 Allow sealant to cure for the stated time, then run water and inspect every connection for leaks. Recheck that the basin is stable and level.

These instructions provide general guidance. Product-specific dimensions and fixing details shown in the current technical specification take precedence.