

INSTALLATION INSTRUCTIONS

S12 Back to Wall Bidet
Product code: AC501204W

Important safety information

Installation must be completed by a competent person in accordance with the Technical Specification and local plumbing and building requirements. Inspect every ceramic component before fitting; do not install a chipped, cracked or damaged product.

Installation sequence

- 1 Plan services. Confirm the finished position, hot/cold water supplies, waste route and all dimensions in the Technical Specification. Select the compatible tap or mixer, waste and trap; these are sold separately.
- 2 Prepare fittings. Inspect the ceramic. Fit the tap/mixer and waste where access is easiest, following their manufacturers' instructions and using non-staining seals.
- 3 Dry-fit the bidet. Position the bidet with its back correctly aligned to the wall. Confirm it is level and that supply and waste connections engage without stress.
- 4 Secure. Mark and drill approved fixing positions, avoiding concealed services. Use sanitary-ware fixings with protective washers and do not overtighten ceramic.
- 5 Connect and seal. Connect water and waste, then apply neutral-cure sanitary silicone neatly at wall and floor junctions while preserving service access.
- 6 Test. Run hot and cold water, verify drainage and inspect all joints for leaks. Allow sealant to cure fully before use.

Supplied: Ceramic bidet.

Sold separately: Tap or mixer, waste, trap, water connections and installation consumables.