

INSTALLATION INSTRUCTIONS

S16 Wall Hung Bidet
Product code: AC501605W

Important safety information

Installation must be completed by a competent person in accordance with the Technical Specification and local plumbing and building requirements. Inspect every ceramic component before fitting; do not install a chipped, cracked or damaged product.

Installation sequence

- 1 Install structural support. Install a compatible bidet support frame or structural fixing system in accordance with its manufacturer's instructions. Confirm the wall can carry the complete installed load.
- 2 Plan services. Set hot/cold supplies, waste and fixing centres to the Technical Specification. Select the compatible tap or mixer, waste and trap; these are sold separately.
- 3 Close and finish the wall. Pressure-test services before closing the wall. Finish the surface flat, leaving rods and connections correctly positioned and protected.
- 4 Prepare and mount. Inspect the ceramic and pre-fit accessible components. Use two people where required; engage the bidet squarely, fit protective washers and tighten evenly without overstressing ceramic.
- 5 Connect and seal. Connect water and waste without pipe strain. Apply neutral-cure sanitary silicone at the wall junction while retaining required service access.
- 6 Test. Run hot and cold water, verify drainage and check every joint for leaks. Confirm the unit is level and rigid before use.

Supplied: Ceramic bidet.

Sold separately: Compatible support frame/fixings, tap or mixer, waste, trap and water connections.