

INSTALLATION INSTRUCTIONS

S18 Wall Hung WC Rimless with Soft-Close Seat
Product code: AC501803BLK

Important safety information

Installation must be completed by a competent person in accordance with the Technical Specification and local plumbing and building requirements. Inspect every ceramic component before fitting; do not install a chipped, cracked or damaged product.

Installation sequence

- 1 Install the support system. Install a compatible certified carrier frame, concealed cistern and flush control in accordance with their manufacturers' instructions. These components are sold separately.
- 2 Verify the finished position. Before closing the wall, pressure-test the cistern and confirm frame height, level, fixing centres, flush pipe and soil outlet against the Technical Specification.
- 3 Prepare the connections. Finish the wall, cut connection pipes to the support-system instructions and fit all protective sleeves and seals. Do not transfer pipe strain to the ceramic.
- 4 Mount the WC. Use two people where required. Slide the pan squarely onto the frame rods and connections, fit protective washers and tighten the retaining hardware evenly.
- 5 Fit the seat and seal. Fit and align the soft-close seat. Apply a neat bead of neutral-cure sanitary silicone at the wall junction without blocking required service access.
- 6 Test and approve. Operate both flush settings repeatedly and inspect every connection for leakage. Confirm the pan is level and rigid before use. The allowable load is governed by the complete certified support installation.

Supplied: Ceramic WC pan with soft-close seat.

Sold separately: Compatible certified carrier frame, concealed cistern, flush control/plate and installation consumables.