

INSTALLATION INSTRUCTIONS

WC-50 Urinal
Product code: AC505001W

Important safety information

Installation must be completed by a competent person in accordance with the Technical Specification and local plumbing and building requirements. Inspect every ceramic component before fitting; do not install a chipped, cracked or damaged product.

Installation sequence

- 1 Plan the installation. Confirm mounting height, fixing centres, water inlet and waste position from the Technical Specification. Select a compatible flushing supply/control, waste connection and support system; these are sold separately.
- 2 Prepare structure and services. Provide sound structural support and route the flush inlet and waste. Pressure-test concealed services before closing the wall.
- 3 Finish and mark. Complete a flat finished wall, transfer the approved fixing centres and avoid concealed pipes or cables when drilling.
- 4 Mount the urinal. Inspect the ceramic, fit compatible seals and lift the urinal squarely into position. Use protective washers and tighten fixings evenly without overstressing ceramic.
- 5 Connect and seal. Connect the flush inlet and waste without pipe strain. Seal the wall junction neatly with neutral-cure sanitary silicone while preserving service access.
- 6 Test. Operate the selected flush control repeatedly. Confirm even rinsing, free drainage and leak-free joints before use.

Supplied: Ceramic urinal body.

Sold separately: Compatible flushing supply/control, waste connection, support/fixings and installation consumables.